

4K Ultra HD

New generation SONY 1 / 2.5-inch high-resolution UHD CMOS sensor with a maximum of 8.51 million pixels, which enables 4K (3840×2160) ultra-high-resolution high-quality images, downward compatibility including 1080P, 720P and other resolutions.

Remote control

RS232, network and USB can be used to control the camera.



12X Optical zoom + 16X Digital Zoom

Use 71° wide-angle high quality lens, support 12x optical zoom, and 16x digital zoom.

Double stream

At the same time support two streams of stream output (YUY2, MJPEG, H.264 two), to reduce the host codec pressure.

H.264 Slice/ H.264 SVC encoding support

The output H.264 stream supports Slice and SVC encoding modes for high-end USB conferencing video applications.

Full-featured Multi interface

Full function HDMI + SDI + IP + USB four-channel simultaneous outputs, compatibility USB 2.0, support compressed video output, support UVC protocol.

Low illumination

New CMOS image sensor with ultra-high SNR can effectively reduce the image noise under low illumination. At the same time, the 2D and 3D noise reduction algorithms are applied to greatly reduce the noise. Even under ultra-low illumination, the picture is still clean and clear.

TECHNICAL SPECIFICATIONS

Model Candypop - CP12XA

Type PTZ Camera

Resolution 4K @ 60fps, 1080P @ 60fps, 720P @ 60fps

Video Format H.264 AVC, H.264 SVC, H.265, MJPEG

Optical Zoom 12X (f 4.4mm ~ 52.8mm, F1.8 ~ F2.6)

Digital Zoom 16X

Minimal Illumination 0.05 Lux @ (F1.8, AGC ON)

White Balance Automatic, one-click, manual

Backlight Compensation Support

Video S/N ≥55dB

Digital Noise Reduction 2D&3D Digital Noise Reduction

Sensor 1 / 2.5", CMOS, Effective Pixel: 8.51M

PAN Range ±170°

Tilt Range -30° ~ +30°

Horizontal Angle of view 71 ° ~ 8.2 °

Vertical Angle of view 42.7 ° ~ 4.5 °

Input/Output Interface HDMI, USB 3.0, LAN(RJ-45), RS232, 3G-SDI, Line In

Operating System Support Windows, Mac OS X, Linux, Android

No. of Preset 255 Preset

Input Voltage DC 12V

Power Consumption 12W (Max)

Operating Temperature -10 ° C ~ 40 ° C

Dimension (W X H X D) 200mm x 176mm x 130mm

Net Weight 1.41 Kg



admin@techocean.co.in



No 3054, Z Block 4th street, 13th Main Road, Annanagar, Chennai - 600 040. Tamilnadu, India.



