

CANDYPOP CP4SB



All-in-one design

The three-in-one design of 4K ultra HD camera, beamforming microphone and full-frequency loudspeaker reduces wiring and makes video communication easy.

4K UHD

Using 1/2.5 inch, 8.51M pixel high quality UHD CMOS sensor, 4K (3840x2160) @p30fps ultra high resolution clear image, and downward compatible with 1080P, 720P and other resolutions. Can meet the needs of users for different video experiences, and can provide clearer, real, smooth and accurate communication.

Beamforming microphone

4 PCS Beam Forming (BF) microphone array are built in, with a pickup distance of 6 meters. Low-distortion transverse beamforming algorithm can direct the microphone directly to the speaker, with better sound, clearer communication, fuller and more authentic.

Audio 3A algorithm

Built-in audio 3A algorithm (AEC/AGC/ANS), full duplex dialogue, can meet the communication needs of different room structures, whether sitting at a conference table, sitting against the wall or standing, can have comfortable experience for calling.

Plug and play type

Through plug and play USB interface connect with the computer or business display screen, very easy to use. Less wiring, convenient video communication, reduce the user's learning cost.

Rich interfaces

Support HDMI 2.0 and USB 3.0 audio video output simultaneously.

Applicable scene

It is specially designed for small and medium-sized meeting rooms, especially for the Huddle Room with 4 to 6 people, to help enterprises re-tap the potential of using the small and micro meeting space inside. On one hand, it can hold meetings more efficiently, on the other hand, it can also save the rental cost.

Product value

It is convenient for small and medium-sized enterprises to conduct daily business negotiation and team cooperation in different places flexibly, so as to create a relaxed, free and smooth conversation environment, make decisions quickly and improve efficiency.

Wide FOV

121°wide field of view (110° horizontal field of view), 5 times zoom, optical lens customized for the conference scene, built-in electric head (horizontal and pitch $\pm 15^\circ$ motion range), no need to worry about the camera position, participants can easily enter the scene clearly.

Intelligent analysis

Built-in intelligent analysis algorithm, listening to the speaker position, automatic framing of participants, automatic tracking of speakers, switching the speaker screen, to ensure that the speaker is always clearly in the picture.

Full frequency speaker

Full frequency Hi-Fi loudspeaker, professional acoustics design, reduce noise interference, provide outstanding sound effect.

Easy installation

Flexible installation options such as countertops, walls, and TV/display screens are available for quick installation and deployment in a crowded meeting room.

CAMERA	
Video System	4K@30fps, 1080P@30fps, 720P@60fps, 720P@30fps
Sensor	1/2.5 inch, CMOS, 8.51M pixel
Lens	120° (DFOV) , 110° (HFOV) , 5x zoom, pan/tilt ±15°
PTZ	MPT + EPTZ
Digital Noise Reduction	2D & 3D digital noise reduction
Video S/N	≥55dB
Backlight Compensation	Support
AUDIO	
Full frequency speaker	96 dB SPL in the case of 0.5 meter
Microphone array	Beamforming microphone, pick up distance up to 6 meters
External MIC	Support (Optional, extral cost)
USB FEATURES	
Connection type	USB 3.0, downward compatible with USB2.0
Video Compression	H.264 / MJPEG / YUY2 / NV12
USB audio	32K sampling rate, support UAC2.0
USB video communication protocol	UVC 1.1~1.5
UVC PTZ control	Support
SYSTEM COMPATIBILITY	
OS	Windows 7 (only 1080p and below), Windows 8.1, Windows 10 or higher macOS® 10.10 or higher Google Chromebook™ Version 29.0.1547.70 or higher Linux (requires support for UVC) Android
Hardware platform	2.4 GHz Intel® Core 2™ Duo processor or higher 2 GB of memory or higher USB 2.0 interface (4K video output need USB 3.0 interface)
INPUT/OUTPUT INTERFACE	
HD output	1 * HDMI , version 2.0 ;
USB interface	1 * USB3.0, Type C ; 1 * USB2.0, Type A ;
Wireless	Bluetooth
Power jack	DC 12V, 2A (MAX)
OTHERS	
Control mode	2.4G remote controller
Installation mode	Support for desktop, wall, TV, and other installation options
Standard cable	USB3.0 (2 meters)
Safety protection	Security lock jack
GENERIC SPECIFICATION	
Remote	2.4G remote controller
Operating Temperature	0°C ~ 40°C
Storage Temperature	-40°C ~ 60°C
Size	600mm * 140mm * 115mm (holder included)
Net Weight	2.5 Kg
Adaptable application	LCP (Zoom, Blue Jeans, Broad soft, Starleaf, Pexip, Vidyo and all UVC application (Google Hangouts, Go to Meeting, etc)



admin@techocean.co.in



No 3054, Z Block 4th street, 13th Main Road, Annanagar,
Chennai – 600 040. Tamilnadu, India.



99 620 37471
044-43627470



techocean.co.in